



2481

**InterCal Croatia d.o.o., Ruđera Boškovića 52, 43 541 Sirač, Republic of Croatia
Quarry Čardak, Ličko Lešće 3, 53 220 Otočac, Republic of Croatia**

22

2481-CPR-0278
4th revision

HRN EN 13242:2008 (EN 13242:2002+A1:2007)

**Aggregate for unbound and hydraulically bound materials for use in civil engineering work
and road construction**

Particle shape - shape index	Category	SI₂₀
Particle size	Designation	0/63 mm
Particle size - tolerance category	Category	G_{A75}, G_{A80}, G_{A85}
Particle density – apparent	Declared value	2,71 Mg/m³
Particle density – with pores, dry	Declared value	2,65 Mg/m³
Particle density – saturated, surface dry	Declared value	2,67 Mg/m³
Fines content	Category	f₃
Percentage of crushed particles	Category	C_{90/3}
Resistance to fragmentation/crushing	Category	LA₂₅
Water absorption/suction	Declared value	0,8 %
Acid soluble sulfates	Category	AS_{0,2}
Total sulfur	Category	S₁
Humus	Declared value	none
Resistance to wear (micro-Deval)	Category	M_{DE}15
Water absorption	Category	WA₂₄1
Durability against freeze-thaw	Declared value	resistant
Petrographic description	Declared value	Limestone aggregate

This CE mark is related to Declaration of Performance number 2481-CPR-0278 (4.)-8/22.