

TECHNICAL GUIDANCE

Product	Aggregate fraction 8/16 mm	
Substance name	Limestone; calcium carbonate CaCO ₃	
Manufacturer	InterCal Croatia d.o.o., Ruđera Boškovića 52, 43 541 Sirač Kamenolom Čardak, Ličko Lešće 3, 53 220 Otočac tel: + 385 (0)43 322 129, fax: + 385 (0)43 442 015, e-mail: info@intercal.hr	
Use	Production of concrete, reinforced concrete, prestressed concrete, concretes of all compressive strength grades and concretes of all exposure grades, depending on environmental effects.	
Technical characteristics and properties (according to HRN EN 12620:2008)	see Declaration of Performance	
Packaging	Bulk	
Storage	No limitations	
Expiration date	Not limited	
Transport	Product is not classified as hazardous for transport by road or rail. Prevent dusting of material during transport.	
Safety measures Waste management	pecial protective equipment is not necessary for work in safe manner. ccording to Regulation on Categories, Types and Classification of /aste, rest of the material has to be classified as waste of key number 1 04 08.	
Factory production control	Initial inspection of factory and of factory production control as well as continuous surveillance, assessment and approval of factory production control is conducted by CSS d.o.o	

	NAME	DATE
WRITTEN BY	Kornelija Bogdan	2020-12-17
APPROVED BY	Mihael Polenus	2020-12-17