

TECHNICAL GUIDANCE

Rev. form: 1

OB-82.43

Product Aggregate fraction 4/8 mm

Substance name Limestone; calcium carbonate CaCO₃

InterCal Croatia d.o.o., Ruđera Boškovića 52, 43 541 Sirač Manufacturer

> Kamenolom Čardak, Ličko Lešće 3, 53 220 Otočac tel: + 385 (0)43 322 129, fax: + 385 (0)43 442 015,

e-mail: info@intercal.hr

Production of concrete, reinforced concrete, prestressed concrete, Use

concretes of all compressive strength grades and concretes of all

exposure grades, depending on environmental effects.

Technical characteristics

and properties

(according to HRN EN

12620:2008)

see Declaration of Performance

Packaging Bulk

Storage No limitations

Expiration date Not limited

Transport Product is not classified as hazardous for transport by road or rail.

Prevent dusting of material during transport.

Safety measures

Waste management

Special protective equipment is not necessary for work in safe manner. According to Regulation on Categories, Types and Classification of Waste, rest of the material has to be classified as waste of key number

01 04 08.

Factory production

control

Initial inspection of factory and of factory production control as well as

continuous surveillance, assessment and approval of factory

production control is conducted by CSS d.o.o..

	NAME	DATE
WRITTEN BY	Kornelija Bogdan	2020-12-17
APPROVED BY	Mihael Polenus	2020-12-17